Green Pin® Snatch Block S

Snatch block type 601S with Green Pin® Shackle attached



P-6951





- **Material:** carbon steel, fitted with conical roller bearings
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted
- **Certification:** 2.1 2.2 MTC [b] CE
- **Note:** Working Load Limit is on the headlifting

working load limit	diameter wire rope	diameter outside sheave	length	width	width outside	weight each
t	mm	a mm	b mm	c mm	d mm	kg
2	7 - 9	75	293	75	82	3.9
4	10 - 12	115	363	102	120	6.4
4	12 - 14	152	417	102	160	8.4
8	14 - 16	152	477	118	160	14.3
12	14 - 16	152	555	147	160	20
8	20 - 22	152	477	118	160	14.1
12	20 - 22	152	555	147	160	20
15	24 - 26	152	585	162	160	24
4	10 - 12	203	478	102	210	11
12	14 - 16	203	580	147	210	27
8	20 - 22	203	526	118	210	18
12	20 - 22	203	580	147	210	28
15	24 - 26	203	646	162	210	30
8	14 - 16	254	582	118	260	26
8	20 - 22	254	582	118	260	26
12	20 - 22	254	680	147	260	35
15	24 - 26	254	705	162	260	42
8	20 - 22	305	612	118	310	31
12	20 - 22	305	745	147	310	53
15	24 - 26	305	771	162	310	55
8	20 - 22	357	662	118	360	31
12	20 - 22	357	770	147	360	60
15	24 - 26	357	798	162	360	63
22	28 - 32	357	906	216	385	126
8	20 - 22	406	712	118	410	35
12	20 - 22	406	820	147	410	67
15	24 - 26	406	848	162	410	70
22	28 - 32	406	963	216	415	139
8	20 - 22	457	762	118	460	42
12	20 - 22	457	878	147	460	75
15	24 - 26	457	898	162	460	78
22	28 - 32	457	1033	216	465	154
30	28 - 32	457	1083	238	468	218

continued on next page >

Green Pin® Snatch Block S (continued)

Snatch block type 601S with Green Pin® Shackle attached



P-6951





- **Material:** carbon steel, fitted with conical roller bearings
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted
- **Certification:** 2.1 2.2 MTC [b] CE
- **Note:** Working Load Limit is on the headlifting

In inch

working load limit	diameter wire rope	diameter outside sheave	length	width	width outside	weight each
t	inch	a inch	b inch	c inch	d inch	lbs
2	9/32 - 3/8	3	11 9/16	3	3 1/4	8.60
4	3/8 - 1/2	4 1/2	14 9/32	4	4 23/32	14.11
4	1/2 - 9/16	6	16 7/16	4	6 9/32	18.52
8	9/16 - 5/8	6	18 25/32	4 5/8	6 9/32	31.5
12	9/16 - 5/8	6	21 7/8	5 25/32	6 9/32	44.1
8	3/4 - 7/8	6	18 25/32	4 5/8	6 9/32	31.1
12	3/4 - 7/8	6	21 7/8	5 25/32	6 9/32	44.1
15	1	6	23 1/32	6 3/8	6 9/32	52.9
4	3/8 - 1/2	8	18 13/16	4	8 9/32	24.3
12	9/16 - 5/8	8	22 13/16	5 25/32	8 9/32	59.5
8	3/4 - 7/8	8	20 23/32	4 5/8	8 9/32	39.7
12	3/4 - 7/8	8	22 13/16	5 25/32	8 9/32	61.7
15	1	8	25 7/16	6 3/8	8 9/32	66.1
8	9/16 - 5/8	10	22 29/32	4 5/8	10 1/4	57.3
8	3/4 - 7/8	10	22 29/32	4 5/8	10 1/4	57.3
12	3/4 - 7/8	10	26 3/4	5 25/32	10 1/4	77.2
15	1	10	27 3/4	6 3/8	10 1/4	92.6
8	3/4 - 7/8	12	24 3/32	4 5/8	12 3/16	68.3
12	3/4 - 7/8	12	29 5/16	5 25/32	12 3/16	116.8
15	1	12	30 5/16	6 3/8	12 3/16	121.3
8	3/4 - 7/8	14	26 1/32	4 5/8	14 5/32	68.3
12	3/4 - 7/8	14	30 9/32	5 25/32	14 5/32	132.3
15	1	14	31 3/8	6 3/8	14 5/32	138.9
22	1 1/8 - 1 1/4	14	35 21/32	8 1/2	15 5/32	277.8
8	3/4 - 7/8	16	27	4 5/8	16 5/32	77.2
12	3/4 - 7/8	16	32 9/32	5 25/32	16 5/32	147.7
15	1	16	33 3/8	6 3/8	16 5/32	154.3
22	1 1/8 - 1 1/4	16	37 29/32	8 1/2	16 11/32	306.5
8	3/4 - 7/8	18	29 31/32	4 5/8	18 1/8	92.6
12	3/4 - 7/8	18	34 9/16	5 25/32	18 1/8	165.3
15	1	18	35 11/32	6 3/8	18 1/8	172.0
22	1 1/8 - 1 1/4	18	40 21/32	8 1/2	18 5/16	339.5
30	1 1/8 - 1 1/4	18	42 5/8	9 3/8	18 7/16	480.6